















## Technical specifications

# MARMOLEUM® easy loc

Marmoleum easy loc meets the requirements of EN 548

|   |                             |             |                                |
|---|-----------------------------|-------------|--------------------------------|
|     | Classification              | EN 548      | 23/32                          |
|    | Dimensions (length x width) | EN 427      | 123,5 cm x 19,1 cm (per panel) |
|    | Total thickness             | EN 649      | 9.8 mm                         |
|    | Thickness wear layer        | EN 428      | 2 mm                           |
|    | Static charge               | EN 1815     | < 2 kV                         |
|    | Slip resistance             | DIN 51130   | R9                             |
|   |                             | EN 13893    | DS: > 0.30                     |
|    | Fire rating                 | EN 13501-1  | Cfl/s1                         |
|    | Castor chair resistance     | EN 425      | ✓                              |
|    | Residual indentation        | EN 433      | ± 0.07 mm, typical value       |
|    | Colour fastness             | ISO 105-B02 | ✓                              |
|    | Cigarette resistance        | EN 1399     | ✓                              |
|   | Chemical resistance         | EN 423      | ✓                              |
|  | Bacteriostatic properties   | EN ISO 846  | ✓                              |
|  | Life Cycle Assessment       |             | ✓                              |

The above information is subject to modifications for the benefit of further improvements.